

【食器洗い乾燥機 総合カタログ2009 I 誤記のお詫びと訂正】

リンナイ株式会社 2009.4月

日頃はリンナイ製品をご愛用いただき、誠にありがとうございます。
 この度、弊社「食器洗い乾燥機 総合カタログ2009 I」カタログにおいて、記載に誤りがありました。
 謹んでお詫び申し上げますとともに、以下のとおり訂正させていただきます。

《訂正内容》

頁	項目																																																																																																																																												
15	<p>■機能一覧・仕様</p> <p style="text-align: center; font-size: 2em; color: red;">誤</p> <table border="1"> <tr> <td>外形寸法/高さ×幅×奥行(mm)</td> <td>450×448×620.5</td> <td>450×448×620.5</td> <td>450×598×639</td> <td>450×448×620.5</td> <td>450×448×589</td> </tr> <tr> <td>質量(kg)</td> <td>約23</td> <td>約22</td> <td>約26</td> <td>約21.5</td> <td>約21</td> </tr> <tr> <td>使用電源</td> <td colspan="5">AC100V 50/60Hz共用</td> </tr> <tr> <td rowspan="3">消費電力</td> <td>モーター</td> <td>125W(50Hz・60Hz)</td> <td>80W(50Hz)/110W(60Hz)</td> <td>65W(50Hz)/85W(60Hz)</td> <td>80W(50Hz)/110W(60Hz)</td> </tr> <tr> <td>ヒーター</td> <td>800W(洗浄・乾燥時)600W(スチーム時)</td> <td></td> <td>800W</td> <td></td> </tr> <tr> <td>最大</td> <td>925W(50Hz・60Hz)</td> <td>880W(50Hz)/910W(60Hz)</td> <td>865W(65Hz)/885W(60Hz)</td> <td>880W(50Hz)/910W(60Hz)</td> </tr> <tr> <td>給水方式</td> <td colspan="5">給水・給湯兼用(給湯は70℃以下)</td> </tr> <tr> <td rowspan="5">運転制御方式</td> <td>洗浄方式</td> <td colspan="5">回転ノズル噴射による加熱洗浄方式</td> </tr> <tr> <td>標準使用水量</td> <td>約14L(重曹洗浄モード)約12L(専用洗剤洗浄モード)</td> <td>約15L</td> <td>約11.5L</td> <td>約9.5L</td> </tr> <tr> <td>乾燥方式</td> <td colspan="5">ヒーター間欠通電十強制送風</td> </tr> <tr> <td>温度制御方式</td> <td colspan="5">サーミスタによる制御</td> </tr> <tr> <td>水位検知</td> <td colspan="5">水位スイッチによるマイコン制御</td> </tr> </table> <p style="text-align: center; font-size: 2em; color: red;">正</p> <table border="1"> <tr> <td>外形寸法/高さ×幅×奥行(mm)</td> <td>450×448×620.5</td> <td>450×448×620.5</td> <td>450×598×639</td> <td>450×448×620.5</td> <td>450×448×589</td> </tr> <tr> <td>質量(kg)</td> <td>約23</td> <td>約22</td> <td>約26</td> <td>約21.5</td> <td></td> </tr> <tr> <td>使用電源</td> <td colspan="5">AC100V 50/60Hz共用</td> </tr> <tr> <td rowspan="3">消費電力</td> <td>モーター</td> <td>125W(50Hz・60Hz)</td> <td></td> <td>65W(50Hz)/85W(60Hz)</td> <td>80W(50Hz)/110W(60Hz)</td> </tr> <tr> <td>ヒーター</td> <td>800W/600W ※4</td> <td></td> <td>800W</td> <td></td> </tr> <tr> <td>最大</td> <td>925W(50Hz・60Hz)</td> <td></td> <td>865W(65Hz)/885W(60Hz)</td> <td>880W(50Hz)/910W(60Hz)</td> </tr> <tr> <td>給水方式</td> <td colspan="5">給水・給湯兼用(給湯は70℃以下)</td> </tr> <tr> <td rowspan="5">運転制御方式</td> <td>洗浄方式</td> <td colspan="5">回転ノズル噴射による加熱洗浄方式</td> </tr> <tr> <td>標準使用水量</td> <td>約14L/約12L ※5</td> <td>約15L</td> <td>約11.5L</td> <td>約9.5L</td> </tr> <tr> <td>乾燥方式</td> <td colspan="5">ヒーター間欠通電十強制送風</td> </tr> <tr> <td>温度制御方式</td> <td colspan="5">サーミスタによる制御</td> </tr> <tr> <td>水位検知</td> <td colspan="5">水位スイッチによるマイコン制御</td> </tr> </table>	外形寸法/高さ×幅×奥行(mm)	450×448×620.5	450×448×620.5	450×598×639	450×448×620.5	450×448×589	質量(kg)	約23	約22	約26	約21.5	約21	使用電源	AC100V 50/60Hz共用					消費電力	モーター	125W(50Hz・60Hz)	80W(50Hz)/110W(60Hz)	65W(50Hz)/85W(60Hz)	80W(50Hz)/110W(60Hz)	ヒーター	800W(洗浄・乾燥時)600W(スチーム時)		800W		最大	925W(50Hz・60Hz)	880W(50Hz)/910W(60Hz)	865W(65Hz)/885W(60Hz)	880W(50Hz)/910W(60Hz)	給水方式	給水・給湯兼用(給湯は70℃以下)					運転制御方式	洗浄方式	回転ノズル噴射による加熱洗浄方式					標準使用水量	約14L(重曹洗浄モード)約12L(専用洗剤洗浄モード)	約15L	約11.5L	約9.5L	乾燥方式	ヒーター間欠通電十強制送風					温度制御方式	サーミスタによる制御					水位検知	水位スイッチによるマイコン制御					外形寸法/高さ×幅×奥行(mm)	450×448×620.5	450×448×620.5	450×598×639	450×448×620.5	450×448×589	質量(kg)	約23	約22	約26	約21.5		使用電源	AC100V 50/60Hz共用					消費電力	モーター	125W(50Hz・60Hz)		65W(50Hz)/85W(60Hz)	80W(50Hz)/110W(60Hz)	ヒーター	800W/600W ※4		800W		最大	925W(50Hz・60Hz)		865W(65Hz)/885W(60Hz)	880W(50Hz)/910W(60Hz)	給水方式	給水・給湯兼用(給湯は70℃以下)					運転制御方式	洗浄方式	回転ノズル噴射による加熱洗浄方式					標準使用水量	約14L/約12L ※5	約15L	約11.5L	約9.5L	乾燥方式	ヒーター間欠通電十強制送風					温度制御方式	サーミスタによる制御					水位検知	水位スイッチによるマイコン制御				
外形寸法/高さ×幅×奥行(mm)	450×448×620.5	450×448×620.5	450×598×639	450×448×620.5	450×448×589																																																																																																																																								
質量(kg)	約23	約22	約26	約21.5	約21																																																																																																																																								
使用電源	AC100V 50/60Hz共用																																																																																																																																												
消費電力	モーター	125W(50Hz・60Hz)	80W(50Hz)/110W(60Hz)	65W(50Hz)/85W(60Hz)	80W(50Hz)/110W(60Hz)																																																																																																																																								
	ヒーター	800W(洗浄・乾燥時)600W(スチーム時)		800W																																																																																																																																									
	最大	925W(50Hz・60Hz)	880W(50Hz)/910W(60Hz)	865W(65Hz)/885W(60Hz)	880W(50Hz)/910W(60Hz)																																																																																																																																								
給水方式	給水・給湯兼用(給湯は70℃以下)																																																																																																																																												
運転制御方式	洗浄方式	回転ノズル噴射による加熱洗浄方式																																																																																																																																											
	標準使用水量	約14L(重曹洗浄モード)約12L(専用洗剤洗浄モード)	約15L	約11.5L	約9.5L																																																																																																																																								
	乾燥方式	ヒーター間欠通電十強制送風																																																																																																																																											
	温度制御方式	サーミスタによる制御																																																																																																																																											
	水位検知	水位スイッチによるマイコン制御																																																																																																																																											
外形寸法/高さ×幅×奥行(mm)	450×448×620.5	450×448×620.5	450×598×639	450×448×620.5	450×448×589																																																																																																																																								
質量(kg)	約23	約22	約26	約21.5																																																																																																																																									
使用電源	AC100V 50/60Hz共用																																																																																																																																												
消費電力	モーター	125W(50Hz・60Hz)		65W(50Hz)/85W(60Hz)	80W(50Hz)/110W(60Hz)																																																																																																																																								
	ヒーター	800W/600W ※4		800W																																																																																																																																									
	最大	925W(50Hz・60Hz)		865W(65Hz)/885W(60Hz)	880W(50Hz)/910W(60Hz)																																																																																																																																								
給水方式	給水・給湯兼用(給湯は70℃以下)																																																																																																																																												
運転制御方式	洗浄方式	回転ノズル噴射による加熱洗浄方式																																																																																																																																											
	標準使用水量	約14L/約12L ※5	約15L	約11.5L	約9.5L																																																																																																																																								
	乾燥方式	ヒーター間欠通電十強制送風																																																																																																																																											
	温度制御方式	サーミスタによる制御																																																																																																																																											
	水位検知	水位スイッチによるマイコン制御																																																																																																																																											